



# TECHNICAL DATASHEET

Product Name	POWERPLUS ATF CVT
Preparation Date	16.06.2023
Revision Date	-
TDS No	
Page Setup	1

## 1. Product Name and Company Introduction

**Product Name:** POWERPLUS ATF CVT

**Manufacturer:** SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

**Address:** Aydınlı KOSB Mah. Kristal Cad. NO:18 İstanbul/TURKEY

**Tel:** 0 (216) 504-0508

**Web:** www.powerplus.com.tr

**E-mail:** info@skoroil.com

## 2. Typical Features

POWERPLUS ATF CVT is a transmission fluid suitable for CVT-type automatic transmissions working with belt and chain drive method. It is a synthetic automatic transmission fluid based on special technology-based oils and additives. It is specially formulated for the continuously variable transmission of passenger cars.

Properties;

- ☑ • Provides effective wear protection even at very low temperatures and under high load, thus extending service life. It extends the life of the automatic transmission and reduces maintenance costs.
- ☑ • Minimizes friction and dissipates heat, thus ensuring smooth gear shifting over a wide operating range
- ☑ • Exceptional oxidation and shear stability ensure reliable performance over long drain intervals.
- ☑ • Excellent performance in cold and very high-temperature operation.

Approvals and Specifications;

• Chrysler Jeep NS-2 • Nissan NS-1 • Daihatsu Ammix CVT • Nissan NS-2 • Dodge CVTF+4 • Nissan NS-3 • GM Dex-CVT • Subaru ECVT • MINI COOPER EXL799 • MMC DIAQUEES ATF SP-III • NISSAN CVT FLUID NS-1 / NS-2 / NS-3 SUBARU I-CVT / I-CVT FG • SUZUKI CVT FLUID 3320 SUZUKI • CVT FLUID GREEN 1/2 • TOYOTA CVT FLUID TC/TE•

Viscosity Class		POWERPLUS ATF CVT
Density 15 °C g/ml	ASTM D-4052	Max.0.870
Flash Point COC, °C	ASTM D-92	Min.205
Kinematic Viscosity mm <sup>2</sup> /s at 100°C	ASTM D-445	5.6-9.3
Viscosity Index	ASTM D-2270	Min.165
Pour Point, °C	ASTMD D-97	Max.-42

\* Values may vary from production to production.