



TECHNICAL DATA SHEET

| | |
|------------------|-------------------------|
| Product Name | POWEPLUS ATF III DEXRON |
| Preparation Date | 18.06.2020 |
| Revision Date | - |
| TDS No | |
| Page Setup | 1 |

1. Product Name and Company Introduction

Product Name: POWEPLUS ATF III DEXRON

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.powerplus.com.tr

E-mail: info@skoroil.com

2. Typical Features

POWEPLUS ATF III DEXRON is an automatic transmission oil developed by blending modern additive combinations, especially to meet the requirements of General Motors Dexron III and Ford Mercon from leading engine manufacturers. It provides superior protection and lubrication for the automatic gearbox over a wide temperature range, as well as can be used in steering and hydraulic units.

Properties

- It minimizes friction over a wide operating temperature range and ensures excellent operation during gear changes.
- Advanced additives protect against corrosion, oxidation, foaming and deposits.
- With its electronic control and superior power transmission features, it meets the expectations of engine manufacturers at the maximum level.
- The high viscosity index perfectly delivers the performance needed in all conditions and minimizes friction.

Approval and Specifications

• General Motors Dexron IIIH General Motors Dexron • IID • GM Type A Suffix A • Ford MERCON® • MB-Approval 236.1, 236.5 • Allison C-4 • Voith H55.6335 • MAN 339 TYP Z1, V1 ZF • TE-ML-02F, 03D, 04D, 09, 11B, 14A, 17C • CAT TO-2

| | | |
|---|-------------|-------------------------|
| Viscosity Class | | POWEPLUS ATF III DEXRON |
| Density 15 °C g/ml | ASTM D-4052 | Max.0.870 |
| Flash Point COC, °C | ASTM D-92 | Min.195 |
| Kinematic Viscosity mm ² /s at 100°C | ASTM D-445 | 6.4-8.9 |
| Viscosity Index | ASTM D-2270 | Min.160 |
| Pour Point, °C | ASTMD D-97 | Max.-40 |

* Values may vary from production to production.