



# TECHNICAL DATA SHEET

Product Name	POWERPLUSGEAR SAE 90 GL-1
Preparation Date	31.01.2020
Revision Date	-
TDS No	
Page Setup	1

## 1. Product Name and Company Introduction

**Product Name:** POWERPLUS GEAR SAE 90 GL-1

**Manufacturer:** SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

**Address:** Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

**Tel:** 0 (216) 504-0508

**Web:** www.powerplus.com.tr

**E-mail:** info@skoroil.com

## 2. Typical Features

**POWERPLUS GEAR SAE 90 GL-1** is a gear oil manufactured for use in automotive gearboxes where there is no overpressure operating at normal load and speed and where oil is recommended at API GL-1 level. They are suitable for use in gear units, synchrometer transmissions and differentials that do not require heavy loads because they do not contain excessive pressure additives.

*Especially*

*r • Protects gears from wear when operating in light, non-overpressure conditions.*

*• Prevents rust and corrosion.*

*• Prevents foam formation and protects the oil film*

*• Does not damage the sealing elements.*

*Approval and Specifications*

*• API GL-1*

Viscosity Class		POWERPLUSGEAR SAE 90 GL-1
Density, @ 15°C g/ml	ASTM D-4052	0.870-0.90
Flash Point COC, °C	ASTM D-92	Min.220
Kinematic Viscosity mm <sup>2</sup> /s at 100°C	ASTM D-445	13.5-18.5
Viscosity Index	ASTM D-2270	Min.90
Pour Point, °C	ASTM D-97	Max -18

\*

Values may vary from production to production