



# TECHNICAL DATASHEET

Product Name	POWERPLUS HD 40
Preparation Date	28.12.2018
Revision Date	-
TDS No	
Page Setup	1

## 1. Product Name and Company Introduction

**Product Name:** POWERPLUS HD 40

**Manufacturer:** SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

**Address:** Aydınlı KOSB Mah. Kristal Cad. No:18 Tuzla/İstanbul

**Tel:** 0 (216) 504-0508

**Web:** www.powerplus.com.tr

**E-mail:** info@skoroil.com

## 2. Typical Features

POWERPLUS HD 40 are general purpose lubricating oils formulated from highly refined high quality mineral base oils. They can be used in all kinds of automotive and industrial applications that do not work under very severe conditions and where lubrication is required.

### PROPERTIES

- Protects the system, prolongs its life, prevents loss of performance.
- It provides good protection by preventing wear that may occur on the parts in the system as a result of the high pressure generated.

### APPROVAL AND SPECIFICATIONS

- API CC/SC

Viscosity Class		POWERPLUS HD 40
Density, @ 15°C g/ml	ASTM D-4052	Max.0.889 g/ml
Flash Point COC, °C	ASTM D-92	Min.230 °C
Kinematic Viscosity mm <sup>2</sup> /s at 100°C	ASTM D-445	16.3-21.9 mm <sup>2</sup> /s
Viscosity Index	ASTM D-2270	Min.115
Pour Point, °C	ASTM D-97	Max.-24

\* Values may vary from production to production