



TECHNICAL DATASHEET

Product Name	POWERPLUS HD 50
Preparation Date	28.12.2018
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: POWERPLUS HD 50

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.powerplus.com.tr

E-mail: info@skoroil.com

2. Typical Features

POWERPLUS HD 50 are general purpose lubricating oils formulated from highly refined high quality mineral base oils. They can be used in all kinds of automotive and industrial applications that do not work under very severe conditions and where lubrication is required.

PROPERTIES

- Protects the system, prolongs its life, prevents loss of performance.
- It provides good protection by preventing wear that may occur on the parts in the system as a result of the high pressure generated.

APPROVAL AND SPECIFICATIONS

- API CC/SC

Viscosity Class		POWERPLUS HD 50
Density, @ 15°C g/ml	ASTM D-4052	Max.0.889 g/ml
Flash Point COC, °C	ASTM D-92	Min.230 °C
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	16.3-21.9 mm ² /s
Viscosity Index	ASTM D-2270	Min.115
Pour Point, °C	ASTM D-97	Max.-24

* Values may vary from production to production