

TECHNICAL DATA SHEET

Product Name	POWERPLUS
	READY TO USE
	ANTIFREEZE -40
Preparation Date	06.09.2019
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: POWERPLUS READY TO USE ANTIFREEZE -40

Manufacturer: Skor Petrokimya Urunleri Sanayi ve Ticaret A.S.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.powerplus.com.tr

E-mail: info@skoroil.com

2. Typical Features

POWERPLUS READY TO USE ANTIFREEZE -40 is an ethylene glycol-based product with special additives. It has been developed to prevent damage to aqueous cooling systems from cold weather conditions. Antifreeze can also be used outside the automotive field. It does not contain nitrates. It is mixed with cooling water to protect cars, trucks, buses and other vehicles from the cold. It is applied in the same way on tractors and construction machinery operating outside the highways. It is used in industrial cold water circulation systems, solar-powered systems, ice skating rinks and similar places.

Properties

- It protects against freezing in winter and overheating in summer.
- Protects the cooling system against rust and corrosion.
- It is compatible with the plastic, rubber and sealing elements in the system.
- It performs very well in all seasons due to its good heat conduction properties.

Approval and Specifications

• VW TL 774 F • MB-325.0 • GM 6277M • Ford WSS-M97B44-D • DEUTZ MWM • MAN- 324 SNF • BS 6580 • Komatsu

		POWERPLUS READY TO USE
		ANTIFREEZE -40
Density 15 °C g/ml	ASTMD 4052	1,0-1,1
Colour		Blue
Smell		Characteristic
Ph (%5)	ASTM D1287	8-10
Freezing Point	ASTM D 1177	< -42°C
Flash point COC, °C	ASTM D 1120	>160 °C

^{*} Values may vary from production to production.

