



# TECHNICAL DATASHEET

Product Name	POWERPLUS MOTORCYCLE 4T 15W40
Preparation Date	31.07.2019
Revision Date	-
TDS No	
Page Setup	1

## 1. Product Name and Company Introduction

**Product Name:** POWERPLUS MOTORCYCLE 4T 15W40

**Manufacturer:** SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

**Address:** Aydınlı KOSB Mah. Kristal Cad. No :18 Tuzla / İstanbul

**Tel:** 0 (216) 504-0508

**Web:** www.powerplus.com.tr

**E-mail:** info@skoroil.com

## 2. Typical Features

POWERPLUS MOTORCYCLE 4T 15W40 is a premium quality motorcycle oil prepared from well-refined mineral base oils. It is safely used in four-stroke and high-performance, air- or water-cooled motorcycles in all four seasons.

Properties

- Thanks to its high and stable viscosity index, it prevents oil film tearing by keeping the viscosity of the oil under control even under severe conditions.
- Oil life is long thanks to its high resistance to abrasion, rust and corrosion.
- Provides low fuel consumption.
- Provides maximum sustainable engine performance with its special formulation that releases power.

Approval and Specifications

- API SJ JASO MA (T903:2011) • JASO MA2 (T903:2011)•

Viscosity Class		POWERPLUS MOTORCYCLE 4T 15W40
Density, @ 15°C g/ml	ASTM D-4052	0,86-0,90
Flash Point COC, °C	ASTM D-92	Min.210
Kinematic Viscosity mm <sup>2</sup> /s at 40°C mm <sup>2</sup> /s at 100°C	ASTM D-445	12.5-16.3
Viscosity Index	ASTM D-2270	Min.120
Pour Point, °C	ASTM D-97	Max.-24

\* Values may vary from production to production.