



TECHNICAL DATA SHEET

Product Name	POWERPLUS MOTORCYCLE 2T
Preparation Date	31.07.2019
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: POWERPLUS MOTORCYCLE 2T

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB Mah. Kristal Cad. No:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.powerplus.com.tr

E-mail: info@skoroil.com

2. Typical Features

POWERPLUS MOTORCYCLE 2T is a mineral-based motorcycle oil specifically designed to provide high performance in two-stroke engines and other small engines. Air- or water-cooled two-stroke engines are used in motorcycles, lawnmowers, and agricultural tools. The fuel/oil mixing ratio should be determined according to the engine manufacturers' recommendations.

Properties

- Thanks to the active cleaning agents inside, it prevents the formation of sediment and sludge. • Ensures efficient operation of the ignition system, increases the quality of combustion.

Approval and Specifications

- API TC • Global GC • JASO FD • T.I.S.I. • ISO-L-EGD

Viscosity Class		POWERPLUS MOTORCYCLE 2T
Density, @ 15°C g/ml	ASTM D-4052	0,86-0,90
Flash Point COC, °C	ASTM D-92	Min.210
Kinematic Viscosity mm ² /s at 40°C mm ² /s at 100°C	ASTM D-445	7,5 – 11,3
Viscosity Index	ASTM D-2270	Min.110
Pour Point, °C	ASTM D-97	Max.-25

* Values may vary from production to production