



TECHNICAL DATASHEET

Product Name	POWERPLUS PREMIUM 10W40 SL/CF
Preparation Date	06.09.2019
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: POWERPLUS PREMIUM 10W40 (SL/CF)

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.powerplus.com.tr

E-mail: info@skoroil.com

2. Typical Features

POWERPLUS PREMIUM 10W40 (SL/CF) is formulated with a combination of synthetic and premium base oils and advanced additive, which is a high quality semi-synthetic multi-grade engine oil for use in the diesel engines of gasoline, LPG and passenger cars, small commercial vehicles, light commercial vehicles. Trucks and vans with or without turbocharging.

Properties;

- With its effective detergent and dispersant additives, it prevents deposit formation and keeps the engine clean.
- It provides fuel economy with its excellent viscosity control feature.
- It binds to the engine surfaces with the smart molecules it contains, creating an additional layer of protection against wear.
- It makes it easy to work in the cold with its low temperature flowability.

Approval and Specifications

- API SL/CF • VW 501.01 / 505.00 • ACEA A3/B3-10 • MB Approval 229.1 • AVTOVAZ LADA CA

Viscosity Class		POWERPLUS PREMIUM 10W40 (SL/CF)
Density, @ 15°C g/ml	ASTM D-4052	0.87-0.89
Flash Point COC, °C	ASTM D-92	Min.220
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	12.5-16.3
Pour Point, °C	ASTMD D-97	Max.-22

* Values may vary from production to production.