



TECHNICAL DATASHEET

Product Name	POWERPLUS PREMIUM 5W40 SM/CF
Preparation Date	02.01.2019
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: POWERPLUS PREMIUM 5W40 SM/CF

Manufacturer: Skor Petrokimya Urunleri Sanayi ve Ticaret A.S.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.powerplus.com.tr

E-mail: info@skoroil.com

2. Typical Features

POWERPLUS PREMIUM 5W40 SM/CF is a fully synthetic motor oil developed by enriching it with synthetic base stocks and qualified additive technology. Recommended for all types of high-performance modern vehicles, passenger cars, multi-point fuel-injected gasoline engines, SUVs and Off-roads. It is recommended not to use any additives with this oil. It is recommended for use in vehicles without diesel particulate filters (DPFs) and gasoline catalytic converters (CATs). Properties;

- Thanks to its synthetic structure, the volatility of the oil is low. This leads to a decrease in fat loss.
- It provides fuel economy with its excellent viscosity control feature.
- It makes it easy to work in the cold with its low temperature flowability.
- It has high resistance to tearing due to its high viscosity index.

Approvals and Specifications; •API SM / API SL • API CF • ACEA A3/B3/B4 • Porsche A40 • Peugeot/Citroën Automobiles B71 2296 • AVTOVAZ (LADA cars) MB-Approval 229.3 • MB-Approval 229.5 Volkswagen • VW50200 Volkswagen • VW50500 Renault RN0700 • Renault RN0710 Opel GM-LL-A-025 • Opel GM-LL-B-025 • BMW Longlife-01•••

Viscosity Class		POWERPLUS PREMIUM 5W40 SM/CF
Density, @ 15°C g/ml	ASTM D-4052	0.840-0.880
Flash Point COC, °C	ASTM D-92	Min 210
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	12,5 – 16,3
Viscosity Index	ASTMD 2270	Min.155
Pour Point, °C	ASTM D-97	Max.-35

* Values may vary from production to production.