



TECHNICAL DATASHEET

Product Name	POWERPLUS PREMIUM 10W30 SN/CF
Preparation Date	18.06.2020
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: POWERPLUS PREMIUM 10W30 SN/CF

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.powerplus.com.tr

E-mail: info@skoroil.com

2. Typical Features

POWERPLUS PREMIUM 10W30 SN/CF is a fully synthetic, all-season engine oil prepared with synthetic base oils and advanced technology performance additive packages.

- Offers long drain intervals and fuel economy.
- Provides effective piston cleaning by preventing piston deposit and deposit formation.
- Protects the environment with exhaust emission control.
- Provides the best efficiency from fuel, increases engine efficiency
- It has high resistance to tearing due to its high viscosity index.
- It prevents the formation of sediment, soot, varnish and deposits.
- Full power and protection from the first start is provided.

Approvals and Specifications;

• API CI-4/CH-4/CG-4/CF-4/CF API • SL/SJ ACEA E7-08 • ACEA A3/B4-10 • MAN M 3275 MB-Approval 228.3 • Caterpillar ECF-2 • Renault RLD-2 JASO DHD-1 • MACK EO-M Plus • Volvo VDS-3 • CUMMINS CES 20076/20077/20078 • MTU Level 2 • Detroit Diesel • Deutz DQC-III-05 • • Global DHD-1 • •

Viscosity Class		POWERPLUS PREMIUM 10W30 SN/CF
Density, 15 °C g/ml	ASTM D-4052	0,85-0,88
Flash Point COC, °C	ASTM D-92	Min.200
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	9,3-12,5
Viscosity index	ASTM D-2270	Min.150
Pour Point, °C	ASTMD D-97	Max. -30

* Values may vary from production to production