



TECHNICAL DATASHEET

Product Name	POWERPLUS PREMIUM 5W20 SL/CF
Preparation Date	02.01.2019
Revision Date	-
TDS No	
Page Setup	1

1. Product Name and Company Introduction

Product Name: POWERPLUS PREMIUM 5W-20 SL/CF

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.powerplus.com.tr

E-mail: info@skoroil.com

2. Typical Features

POWERPLUS PREMIUM 5W-20 SL/CF is an engine oil formulated with advanced oils and high-tech performance additives with the aim of superior protection and excellent flowability. It has been developed for use in gasoline and diesel engines of passenger cars and commercial vehicles. It is also used safely in small commercial vehicles such as cars, vans, minibuses.

Properties;

- Excellent viscosity control provides fuel economy and long service life.
- It facilitates working in the cold with its low temperature flowability.
- It has high resistance to tearing due to its high viscosity index.
- Prevents the formation of sediment, soot, varnish and deposit.

Approvals and Specifications;

- API SL/CF • VW 501.01 / 505.00 • ACEA A3/B3-10 • MB Approval 229.1 • AVTOVAZ LADA cars

Viscosity Class		POWERPLUS PREMIUM 5W-20 SL/CF
Density, @ 15°C g/ml	ASTM D-4052	0.840-0.880
Flash Point COC, °C	ASTM D-92	Min 200
Kinematic Viscosity mm ² /s at 100°C	ASTM D-445	9.3-12.5
Viscosity Index	ASTMD 2270	Min.145
Pour Point, °C	ASTM D-97	Max.-30

* Values may vary from production to production.