



# TECHNICAL DATASHEET

Product Name	POWERPLUS ATF DEXRON VI
Preparation Date	16.06.2023
Revision Date	-
TDS No	
Page Setup	1

## 1. Product Name and Company Introduction

**Product Name:** POWERPLUS ATF DEXRON VI

**Manufacturer:** SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

**Address:** KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

**Tel:** 0 (216) 504-0508

**Web:** www.powerplus.com.tr

**E-mail:** info@skoroil.com

## 2. Typical Features

POWERPLUS ATF DEXRON VI is a superior performance synthetic automatic transmission fluid produced by blending synthetic base stocks and advanced technology additives. It has been developed for use in the new-generation transmissions of passenger cars and light commercial vehicles.

Properties;

- Thanks to its excellent fluidity, it shows high performance at low temperatures.
- Thanks to its high oxidation resistance and thermal stability, it provides superior resistance to aging ensures a long oil change period, and reduces maintenance costs.
- Thanks to its special additives, it extends the life of the transmission by minimizing the wear that may occur in automatic transmissions.
- Thanks to the special additives it contains, it prevents the formation of sediment and does not foam. Provides protection against rust and corrosion.

Approval and Specifications

- General Motors Dexron VI • MB 236.15 , MB 236.16 MB JASO • 1A LV • Honda ATF Type 3.1

Viscosity Class		POWERPLUS ATF DEXRON VI
Density 15 °C g/ml	ASTM D-4052	Max.0.870
Flash Point COC, °C	ASTM D-92	Min.210
Kinematic Viscosity Mm <sup>2</sup> /s at 100°C	ASTM D-445	5.6-9.3
Viscosity Index	ASTM D-2270	Min.153
Pour Point, °C	ASTMD D-97	Max.-40

\* Values may vary from production to production.