

TECHNICAL DATASHEET

Product Name	POWERPLUS	
	TRAC 300	
	10W30	
Preparation Date	18.06.2020	
Revision Date	-	
TDS No		
Page Setup	1	

1. Product Name and Company Introduction

Product Name: POWERPLUS TRAC 300 10W30

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.powerplus.com.tr

E-mail: info@skoroil.com

2. Typical Features

POWERPLUS TRAC 300 10W30 is a multi-purpose transmission oil specially developed for use in tractor and agricultural machinery in automatic transmission, ax, hydraulic, wet brake systems, final drive units and power take-offs.

- Provides high performance in power transmission of moving equipment.
- It has excellent low temperature performance and high temperature performance.
- With its friction regulating insertion, it ensures that the brake system operates with high efficiency and quietness.
- Thanks to its high thermal and oxidation stability with the additive packages it contains, it prevents deposit formation and increases working efficiency.

Approvals and Specifications;

•API CF-4/CE/SF API GL-4 F• ORD M2C159-B MF M1139 M1144 M1145 • ACEA E2•ZFTE-ML 06C•NFE 46803 HV •DIN 51524/3 HVLP • MF M1135 J120C FORD M2C134-D• ZF TE-ML 06E• CASE • MS • • • 1207• •

Viscosity Class		POWERPLUS TRAC 300 10W30
Density, 15 °C g/ml	ASTM D-4052	0,86-0,89
Flash Point COC, °C	ASTM D-92	Min.220
Kinematic Viscosity mm2/s at 100°C	ASTM D-445	9,3-12,5
Viscosity index	ASTM D-2270	Min.110
Pour Point, °C	ASTMD D-97	Max27

^{*} Values may vary from production to production