



TECHNICAL DATASHEET

| | |
|------------------|--------------------------------------|
| Product Name | POWERPLUS WHITE GREASE 0,1,2,3 |
| Preparation Date | 18.09.2018 |
| Revision Date | 05.02.2019 |
| TDS No | |
| Page Setup | 1 |

1. Product Name and Company Introduction

Product Name: POWERPLUS WHITE GREASE 0,1,2,3

Manufacturer: SKOR PETROKİMYA ÜRÜNLERİ SAN. VE TİC. A.Ş.

Address: Aydınlı KOSB. Mah. Kristal Cad. NO:18 İstanbul/TURKEY

Tel: 0 (216) 504-0508

Web: www.powerplus.com.tr

E-mail: info@skoroil.com

2. Typical Features

POWERPLUS WHITE GREASE 0,1,2,3 It is a fibrous, water-resistant and multi-purpose calcium grease produced with quality base oils, performance-enhancing additives. It is suitable for use in low and medium speed bearings with an operating temperature not exceeding 70°C, in low speed flat bearings and chassis applications. Thanks to its additives and fibrous structure, it adheres to metal surfaces and protects the metal and prevents consumption.

| TEST | METHOD | TYPICAL FEATURES | | | |
|---|-----------|------------------|---------|---------|---------|
| | | 0 | 1 | 2 | 3 |
| NLGI | - | 0 | 1 | 2 | 3 |
| COLOUR | - | YELLOW | YELLOW | YELLOW | SARII |
| TYPE | - | CALCIUM | CALCIUM | CALCIUM | CALCIUM |
| PENETRATION, 0.1 mm, 25°C' de 60 pulses | ASTM D217 | 355-385 | 310-340 | 265-295 | 220-250 |
| DROP POINT, °C | ASTM D566 | Min.90 | Min.100 | Min.105 | Min.105 |

*Values may vary from production to production.