



# TECHNICAL DATASHEET

Product Name	POWERPLUS XRD TURBO 10W40
Preparation Date	08.05.2020
Revision Date	-
TDS No	
Page Setup	1

## 1. Product Name and Company Introduction

**Product Name:** POWERPLUS XRD TURBO 10W40

**Manufacturer:** Skor Petrokimya Urunleri Sanayi ve Ticaret A.S.

**Address:** Aydınlı KOSB Mah. Kristal Cad. NO:18 İstanbul/TURKEY

**Tel:** 0 (216) 504-0508

**Web:** www.powerplus.com.tr

**E-mail:** info@skoroil.com

## 2. Typical Features

POWERPLUS XRD TURBO 10W40 is an all-season reliably used engine oil for cars and commercial vehicles running on diesel fuels, produced with high quality mineral-based base oils and advanced performance additives.

Properties

- Its superior fluidity at low temperatures allows for easier start-up.
- Excellent viscosity control ensures fuel economy and long service life
- It has high resistance to tearing due to its high viscosity index.
- Extends oil change intervals even when using high-sulphur fuel.

Approval and Specifications

• API CF-4/SJ • MB 228.1, • ACEA A3/ E5 • CUMMINS :CES200077,76,75,72.71,MAN 3275,Volvo • VDS-2  
RENAULT TURCKS :RD-2, • MTU Level 2 • Mack EOM EOM+ • ALLISON C-4,CAT ECF1

Viscosity Class		POWERPLUS XRD TURBO 10W40
Density 15 °C g/ml	ASTM D-4052	Max.0.880
Flash Point COC, °C	ASTM D-92	Min.220
Kinematic Viscosity mm <sup>2</sup> /s at 100°C	ASTM D-445	12.5-16.3
Viscosity Index	ASTM D-2270	Min.110
Pour Point, °C	ASTMD D-97	Max.-25

\* Values may vary from production to production.